

(12) United States Patent Yusu et al.

(10) Patent No.:

US 6,174,597 B1

(45) Date of Patent:

Jan. 16, 2001

(5 A)	14.6100	TO DECORDING A DRADATIC				
(54)	MAGNETIC RECORDING APPARATUS					
(75)	Inventors:	Kelichiro Yusu, Kawasaki; Katsutaro Ichihara, Yokohama; Hideo Ogiwara, Chigasaki; Akira Kikitsu, Yokohama; Futoshi Nakamura, Ichikawa, all of (JP)				
(73)	Assignee:	Kabushiki Kaisha Toshiba, Kawasaki (JP)				
(*)	Notice:	Under 35 U.S.C. 154(b), the term of this patent shall be extended for 0 days.				
(21)	Appl. No.: 08/900,581					
(22)	Filed:	Jul. 25, 1997				
(30)	Foreign Application Priority Data					
Jul. 26, 1996 (JP) 8-197587 Aug. 29, 1996 (JP) 8-228564 Sep. 2, 1996 (JP) 8-232080 Sep. 4, 1996 (JP) 8-234269						
(51)	Int. Cl.7.	G11B 5/66				
		428/332 ; 428/336; 428/694 B; 428/694 BA; 428/900				
(58)	Field of S	earch 428/694 B, 694 BA, 428/900, 336, 332				
(56)	References Cited					
U.S. PATENT DOCUMENTS						

5,480,694 * 1/1996 Daimon et al. 428/64.1

5,626,941	٠	5/1997	Ouano 428/141
5,679,473	•	10/1997	Murayama et al 428/694 T
5,763,085	٠	6/1998	Atarashi et al 428/403
5,768,075	•	6/1998	Bar-Gadda 360/135
5,774,783	•	6/1998	Kaitsu et al 428/546

FOREIGN PATENT DOCUMENTS

0452876 A2 0797192 A1	10/1991 9/1997	` '
7-98835	4/1995	• •
7-311929	11/1995	ĴΡ).
08255342	10/1996	ÌΡ).


^{*} cited by examiner

Primary Examiner—Leszek Kiliman (74) Attorney, Agent, or Firm—Finnegan, Henderson, Farabow, Garrett, & Dunner L.L.P.

(57) ABSTRACT

A magnetic recording apparatus includes a magnetic recording medium including a substrate and a magnetic recording layer formed on the substrate and having a structure in which magnetic grains are dispersed in a nonmagnetic matrix, a means for recording magnetic information on the magnetic recording medium, and a means for reproducing magnetic information from the magnetic recording medium wherein the magnetic grains are separated from the substrate by a part of the matrix and form a substantially single layer parallel to the main surface of the substrate.

23 Claims, 11 Drawing Sheets



05/21/2004, EAST Version: 1.4.1

Printed by EAST

UserID: GLetscher

Computer: WS11680

Date: 05/21/2004

Time: 22:39

Document Listing

Document	Image pages	Text pages	Error pages	
US 6174597 B1	0	1	0	
Total	0	1	0	

ngle (represented by .phi. in FIG. 10) the side surface of the magnetic grain 22a makes with the surface of the substrate

is 75.degree. or less. This angle is only the average value, and its maximum

value may be about 85.degree.. This angle is preferably 30.degree. to

70.degree., and more preferably 45 to 70.degree..

- (34) To grow the island-like magnetic grain 22a like the one shown in FIG.
- 10, it is effective to form an underlayer 3 having a specific crystal

orientation. A material preferable for forming such a crystalline underlayer

includes Cr, V, Ti, Pt, Pd, Ir, and ZnO. The underlayer may be amorphous as

long as it has surface energy suitable for growing an island-like magnetic

grain. A material preferable for forming such an amorphous underlayer includes

<u>CoZrNb, NiNb, Sb, Ge, and C. If an underlayer</u> made of one of these materials is

formed to have a thickness of 200 nm or less on an arbitrary substrate,

island-like magnetic grains can be easily grown. If no underlayer is disposed,

island-like magnetic grains can be grown on the substrate by optimizing the

deposition conditions.

(35) The magnetic recording layer 2 may contain not only island-like magnetic

grains having an inclined surface with respect to the substrate, but also flat

magnetic grains separated from the island-like magnetic grains